

Essential for safety, the ZEUS 5-9/9-13 G optoelectronic hood protects the welder's face and eyes from UV, infrared and splashes. Fully automatic, the mask switches from clear to tinted state in a fraction of a second as soon as it is primed. Comes with a headband, it frees the welder's hands and offers all the necessary comfort for welding work.

CHARACTERISTICS


- XL screen
- High sensitivity thanks to 4 sensors
- TIG welding > 2A
- External adjustment: shades or grinding
- Interior setting: sensitivity, delay
- Active filter: shades 5-9 / 9-13
- Range 5-9: special low intensity
- True color Technology



Standard LCD screen




TRUE COLOR Technology




TECHNICAL DATA

| | |
|-------------------------------|---|
| Protection UV/IR | DIN 15 |
| Classification | 1/1/1/2 |
| Light shade | 4 |
| Dark shade | 5 > 9 - 9 > 13 |
| Reaction time | 0,20 ms |
| Time to return to clear state | 0,15 > 0,8 sec |
| Viewing area | 100 x 67 mm |
| Power supply | solar + batteries (CR2450) |
| Weight | 560 g |
| Settings | Sensitivity, delay, shade, grinding |
| Light sensor | 4 |
| Applications | MMA 5 ▶ 400 / TIG 2 ▶ 300 / MIG-MAG 5 ▶ 400 |
| Standards | CE / EN 175F / EN 166 / EN 379 |

Delivered with a headband



Sensitivity



Delay



Shade

Grinding

OPTIONS

Carry bag for helmet welding


043299



Antiperspirant - headband

043466

x2




zoom x2

Magnifying glass for Zeus, Spaceview, Ergotech & Alien True Color x1 042780



Lenses



| | |
|-----------------|-------------------|
| | |
| 114 x 133 (x10) | 103,7 x 69,5 (x5) |
| 043893 | 043695 |