## STEEL DENT PULLING EQUIPMENT



## Réf 052208

# **GYSPOT 2600**

GYSPOT 2600, with its 2600 A maximum output current, is the ideal product for dent pulling and straightening of low thickness car body elements (hood, door, roof panel). The product is multifunctional, which makes it a complete solution. Thanks to its low power consumption, it can work on a simple 230V power supply.

### A MULTIFUNCTIONAL DENT PULLER

#### 3 modes available:

- Welding of stars or washers for car body element pulling.
- Welding of wavy wire, ideal to follow a curved profile. (e.g. wheelhouse)
- Contact shrinking, to work on light impacts and for good finishing.

#### **EASY TO USE**

- **Intuitive**, the potentiometer allows to select both the output power and the requested mode.
- **Automatic**, the welding is generated by simply making a contact between the tool and the element to straighten.



#### Delivered as a standard with:

• 1 spot inertia hammer (1,1kg) and 1 star holder tip



3 stars

- 1 contact shrinking tip

• 1 earth pad

Spot 800 trolley
(optional)
Réf: 051331
* *

#### **AUTO** RMS 1<sub>2 MAX</sub> FAM-MATIC detection Α A Α 230V 50/60Hz 16 1800 2600 5,4 OK 20x18x32 14,1

### **Other characteristics:**

 Cable lengths Earth: 1,7 m Gun: 2 m

Power cord: 2 m

Email: contact@gys.fr