

TECHNICAL DATA SHEET

EU-GB

Peter Kwasny GmbH, Heilbronner Strasse 96, 74831 Gundelsheim / Deutschland Telefon: +49 (0) 06269-95-0; Fax: +49 (0) 6269-95-80 internet: www.kwasny.de e-mail info@kwasny.de

Gun Cleaner Prod. No. 680 095

TECHNOLOGY SprayMax®

- High productivity
- Easy application
- Constant atomisation pressure during the total application process
- Finest aerosol dispersion

PRODUCT Special cleaner for the aerosol supported cleaning of spray guns:

- All-purpose cleaner for many solvent based and waterborne paints including two-pack systems
- · Excellent dissolving and cleaning properties

PROCESSING

Proceeding:

Disposal:

Suitable for:

• 1K solvent based paints like basecoats for

automotive refinish

 1K waterborne paints like waterborne basecoats for automotive refinish.

 Two-pack systems like 2K PUR primer surfacers, fillers, topcoats or 2K epoxy systems.

1. After you finished your paint job spray your spraying gun thoroughly empty

- 2. Remove the paint cup and nozzle head.
- 3. Not later than 2 h after you have finalized your paint work rinse the inner part of your spray gun as well as the nozzle head using the lancet on the spray head of the aerosol.
- 4. Drain the spray gun
- 5. Reassemble your spray gun and dry it with compressed air.

The emptied aerosols are suitable for household collection.

collection.

Prod.-No. 680 095 Version 02/2010 page 1 of 2



TECHNICAL DATA SHEET

CHARACTERISTICS

Basis of raw material: Special combination of solvents

Solid content: n/a

VOC value: 750 g/l

Shelf life: 24 months / 20 °C

Remarks: For professional use only

SprayMax® is a registered trade mark of the Peter Kwasny Group.

The information contained in this paper corresponds to our present knowledge and is a guide to our products and their uses. It is not to be understood as a guarantee for certain properties of our products or of their specific applications. The warnings printed on our labels must be respected. Any industrial property rights should be observed.