

Peter Kwasny GmbH, Heilbronner Str. 96
74831 Gundelsheim / Deutschland
Telefon: +496269 95-0, Fax: +496269 95-80
www.spraymax.com / www.kwasny.com / info@kwasny.de

SprayMax® 1K Structure paint DTP grey 400 ml Art. Nr. 680226



Product

Description / Purpose

Special product for imitation of automotive plastic textured surfaces, particularly for plastic bumpers, trim strips and various plastic parts. Quick process as the structure paint can be applied directly on plastic surfaces, without plastic adhesion promoter.

Properties

- different kind of structures can be achieved
- Easy to use
- Dries very quickly
- Excellent adhesion
- Can be topcoated with all conventional 1K basecoat and 2K topcoat systems

Material base

Acrylic resins

Colour

Grey

VOC Value (EU)

681 g/l

Substrate

Polypropylene (PP/EPDM), Polyvinyl Chloride (PVC), Acrylic nitrile butadiene styrene (ABS), Polycarbonate (PC), Polystyrol (PS), Polyoxymethylene (POM), Polyamide (PA) and other Plastics.
Do not apply on Polyethylene (PE).

In case of doubt, the compatibility of the paint for the respective substrate must be pretested and, if necessary, a suitable pre-treatment with SprayMax plastic adhesion promotor (680009) must be chosen.

Sand surfaces if necessary and clean thoroughly with an aqua silicone remover. The damaged area must be dry and free of grease and dust and all rust needs to be removed. Check compatibility and adhesion first on an unobtrusive area.


Processing

Protection measures




Wear personal protection equipment.
(respiratory mask/gloves/goggles)
For more information, see safety data sheet.

Shake




Shake can thoroughly for at least 2 minutes from when the mixing balls are heard.

Spray to test




After shaking the can, test spray and check compatibility with the surface and the colour.

Spraying distance




15 cm - 20 cm
Depending on the desired structure, the spray distance can be varied.

Spray passes




Dry film thickness 60 - 80 µm
(approx. 2 spray coats)

Flash-off time




Flash time: approx. 5 - 10 min between each spray coat.
End flash off time before forced drying: 15 - 20 min.

Processing conditions




Optimum application at 18° C - 25° C and a relative humidity from 40 - 60 %.

Coverage



approx. 0,5 - 0,75 m² at 30 - 40 µm dry film thickness

Drying



TG1 dust dry: 16 min

TG3 dry to touch: approx. 30 min

TG5 fully cured: approx. 24 h

The stated values refer to the above mentioned processing conditions. The level of dryness is determined pursuant to DIN 53150.




IR- drying possible,

Observe equipment description

Continue

Can be topcoated with conventional 1K solventborne and waterborne basecoats and with 2K topcoats after drying time of 35 min at 60° C or 24 h at 20° C.

Finish




After painting, turn the can upside down and spray the valve until empty.

Additional Information

Important Information

Not suitable for plastic parts made from PE. Do not apply to surfaces coated with synthetic resin paints as this could lift and cause ripples in the paintwork underneath. Do not topcoat wet on wet.

Shelf Life



60 months

The usage period refers to an unused can that is stored correctly at a temperature of 15 - 25° C and a relative humidity below 60%. The can must be stored and transported in an upright position in a dry place where it is protected against chemical and mechanical influences. The safety information on the can and all statutory provisions applicable for the storage site must be observed.

Disposal



The completely emptied spray cans must be disposed of in the recycling system. Cans with hardened material must be disposed of as special waste.

Note

For professional use only.

Identification, see safety data sheet.

The contents in this technical data sheet were created with great care and reflect our current state of knowledge. They provide the user with application-specific information and do not promise certain properties. The information is non-binding and we accept no liability for its integrity, accuracy and completeness. They do not relieve the user of their duty to check the suitability of our product for the intended purpose. The warnings printed on our labels must be respected. Our brands and patents are protected by copyright. All rights reserved We reserve the right to update, amend or supplement the content of the information without prior notice.