

SLIM

Ultra-thin rechargeable work light




SLIM is an USB-C rechargeable LED work light that offers the perfect combination of convenience and versatility. It is a 3-in-1 solution that serves as an inspection light, work light, and flashlight - all in one compact and portable handlamp.

With the ultra-thin design of the light strip (only $\varnothing 9$ mm), it is perfect for reaching the most narrow and inaccessible work areas. This makes SLIM ideal for very demanding and difficult inspection jobs.

It has a built-in magnet and hook, as well as a flexible 100 % foldable body that offers flexible positioning options. The design allows for traditional hand-held use, and its compact size ensures portability anywhere. When folded, it easily transforms into a flashlight that provides a firm grip. In addition, a user-friendly battery indicator keeps you informed about the battery level.

Powered by a high efficiency multi-LED design of 20 LEDs, SLIM offers an adjustable light output up to 500 lumen. The top spotlight provides a focused beam of 150 lumen. The OPTILight setting delivers the required illuminance (LUX) in a typical work situation, ensuring optimized light and runtime with a simple touch. This work light provides a constant lumen output performance measured according to the European standard EN 13032-1.



| | SLIM |
|-------------------------------------|---|
| Product number | 03.6211 |
| Light source | High efficiency multi-LED design with 20 LEDs |
| Luminous flux, lumen | 50-500 Spot: 100 |
| OPTILight setting | 500 lux@0.5 m |
| Adjustable light output | 3 levels |
| Beam angle | 110° Spot: 25° |
| CRI | Ra > 80 |
| CCT | 5700 K |
| Operating time max. / min. lumen, h | 2.5/27 |
| Operating time OPTILight, h | 4 |
| Charging time, h | 3.5 |
| Battery | 3.7 V/2600 mAh Li-ion |
| Verified no. of charging cycles | Min. 1000 |
| Protection class | IP30 |
| Rough service | - |
| Impact protection | IK07 |
| Impact resistance | 2 m |
| Cable | 1 m USB-A to USB-C |
| Operating voltage AC | - |
| Charging voltage/current DC | 5 V / 1 A |
| Power consumption | 3.5 W |
| Charger incl. | No |
| Operating temperature | -10 to +40 °C |
| Dimensions | 166 x 46 x 29 mm |
| Net weight | 205 g |





03.6211 SLIM

03.5612 SLIM
Previous version

PRODUCT IMPROVEMENTS

- 13 % efficiency improvement
- 13 % recycled material
- OPTILight functionality
- Dedicated buttons for on/off and brightness levels
- Battery indicator
- Double temperature surveillance to protect the lamp and battery
- Min. 1000 charging cycles
- Warranty extended from 3 to 5 years
- New colour scheme

A pioneering approach that focuses on reinventing the design and functionality of LED work lights and optimizing energy efficiency to the utmost. With a focus on sustainability, traditional standards are rethought, and boundaries are pushed to extend the lifespan of lighting solutions.

